



# CHR16

Type Size: S0

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Ring type terminal

Sample image

## IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

### Rated insulation voltage $U_i$

Voltage (V)	AC / DC
690	AC / DC

### Rated impulse withstand voltage $U_{imp}$

Voltage (kV)	Oversvoltage category	Pollution degree	Supply system	Function
6	III	3	Valid for lines with grounded common neutral termination	switch
4	III	3	Valid for lines with grounded common neutral termination	Switch disconnecter

### Rated uninterrupted current $I_u/I_{th}$

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements
25	55	60	Ambient temperature +55°C during 24 hours with peaks up to +60°C

### Conventional enclosed thermal current $I_{the}$

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	Additional requirements	No. of stages (from - to)	Mounting	Mounting size
25	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C	--	--	--

### Rated operational current $I_e$

Utilization category	Voltage (V)	Current (A)
AC-15	110 - 110	8
AC-15	220 - 240	8
AC-15	380 - 440	5
AC-20A	690	25
AC-21A	20 - 690	25
AC-22A	220 - 440	25
AC-22A	500 - 500	25
AC-22A	660 - 690	25

### Rated operational power

Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-2	220 - 240	3	3	5,50
AC-2	380 - 440	3	3	11
AC-2	500 - 500	3	3	15
AC-2	660 - 690	3	3	13
AC-3	220 - 240	3	3	4
AC-3	380 - 440	3	3	7,50
AC-3	500 - 500	3	3	7,50
AC-3	660 - 690	3	3	7,50
AC-3	110 - 120	1	2	1,50
AC-3	220 - 240	1	2	3
AC-3	380 - 440	1	2	3,70
AC-3	500 - 500	1	2	4
AC-3	660 - 690	1	2	3,70
AC-4	220 - 240	3	3	1,50
AC-4	380 - 440	3	3	3
AC-4	500 - 500	3	3	3
AC-4	660 - 690	3	3	3
AC-4	110 - 120	1	2	0,45
AC-4	220 - 240	1	2	1,10
AC-4	380 - 440	1	2	2,20
AC-23A	220 - 240	3	3	5,50

Rated operational power				
Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-23A	380 - 440	3	3	11
AC-23A	500 - 500	3	3	11
AC-23A	660 - 690	3	3	11
AC-23A	110 - 120	1	2	1,50
AC-23A	220 - 240	1	2	3
AC-23A	380 - 440	1	2	5,50
AC-23A	500 - 500	1	2	5,50
AC-23A	660 - 690	1	2	5,50

Max Fuse Rating IEC		
Fuse characteristic	No. of Fuses	Current (A)
gG	1	35

### UL60947-4-1 , UL508

Rated insulation voltage Ui		
	Voltage (V)	AC / DC
	600	AC

Rated thermal current			
	Current (A)	Ambient temperature (°C)	Additional Text
	25	0 - 40	-

### CSA

Rated insulation voltage Ui		
	Voltage (V)	AC / DC
	600	AC

Rated thermal current			
	Current (A)	Ambient temperature (°C)	Additional Text
	25	0 - 40	-

### GENERAL TECHNICAL INFORMATION

Tightening torque of screws		
	tightening torque (Nm)	tightening torque (lb-in)
	1	8,80

Rated short-time withstand current Icw		
	Time (s)	Current (A)
	1	250


Approbations	
Specification	Marking

EAC	
-----	---

CE marking	
------------	---

UK Directives	
IEC 60947-3; EN 60947-3; VDE 0660 Teil107	<b>IEC 60947-3</b> <b>EN 60947-3</b>

UL 60947-4-1; CSA C22.2 No. 60947-4-1	
---------------------------------------	---

CSA C.22.2 No.14	
------------------	---

GB/T14048.3	
-------------	---

Power loss per pole	
	Power (W)
	2,30

Conditions during transport and storing		
Minimum temperature (°C)	Maximum temperature (°C)	additional requirements
-40	85	In case of temperatures below -5°C no shock load permissible

Shock / Vibration	
Type of oscillation	Values
Resistance to shock	min. 5g, 30ms

Shock / Vibration	
Type of oscillation	Values
Resistance to vibration	IEC 61373 (1999) Category 1, Class B

**General Information**

**Text**

- Use only isolated ringtype cable lugs or forked cable lugs.
- Do not lubricate or treat contacts.
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.
- Terminals with factory fitted jumper links are tightened during production. Take care during installation to ensure factory fitted links are not lost by undoing both sides of linked terminals. After wiring, all terminal screws must be tightened to recommended torque specifications.
- After installation of the switches the spacings between the terminals must be sufficient to fulfill the requirement of the applicable standards.

Operating temperature		
	Min. Temperature [°C]	Max. Temperature [°C]
	-25	60

**ring type terminal dimensions**

A(mm)	H	8,80 mm
-------	---	---------