



Sample image

# L351

**Type Size: S2**
**Classification Contact: Rigid contact bridge**
**Classification Contact Mat: Silver**
**Classification Terminal: Bolt terminal**
**IEC 60947-3 EN 60947-3, VDE 0660 Teil 107**
**Rated insulation voltage Ui**

Voltage (V)	AC / DC
690	AC

**Rated impulse withstand voltage Uimp**

Voltage (kV)	Overvoltage category	Pollution degree	Supply system	Function
6	III	3	Valid for lines with grounded common neutral termination	Switch / Switch disconnecter

**Rated uninterrupted current Iu/Ith**

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements
350	55	60	Ambient temperature +55°C during 24 hours with peaks up to +60°C

**Rated operational current Ie**

Utilization category	Voltage (V)	Current (A)
AC-20A	20 - 690	350
AC-21B	220 - 440	250
AC-21B	500 - 500	250
AC-21B	660 - 690	200

**Rated operational power**

Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-23B	220 - 240	3	3	45
AC-23B	380 - 440	3	3	90
AC-23B	500 - 500	3	3	110
AC-23B	660 - 690	3	3	55

**Max Fuse Rating IEC**

Fuse characteristic	No. of Fuses	Current (A)
aR	1	400

**UL60947-4-1, UL508**
**Rated insulation voltage Ui**

Voltage (V)	AC / DC
600	AC

**Rated thermal current**

Current (A)	Ambient temperature (°C)	Additional Text
350	0 - 40	-

**CSA**
**Rated insulation voltage Ui**

Voltage (V)	AC / DC
600	AC

**Rated thermal current**

Current (A)	Ambient temperature (°C)	Additional Text
350	0 - 40	-

**GENERAL TECHNICAL INFORMATION**
**Tightening torque of screws**

tightening torque (Nm)	tightening torque (lb-in)
25	220

**Rated short-time withstand current Icw**

Time (s)	Current (A)
1	3800


**Approbations**


Specification	Marking
EAC	



CE marking	
------------	---

UK Directives	
IEC 60947-3; EN 60947-3; VDE 0660 Teil107	IEC 60947-3 EN 60947-3

UL 60947-4-1; CSA C22.2 No. 60947-4-1	
---------------------------------------	---

CSA C.22.2 No.14	
------------------	---

Power loss per pole	Power (W)
	15,50

Conditions during transport and storing		
Minimum temperature (°C)	Maximum temperature (°C)	additional requirements
-40	85	In case of temperatures below -5°C no shock load permissible

**General Information**

- Text*
- Cable lug or copper bus must accept M12x20 screw.
  - Do not lubricate or treat contacts.
  - Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.
  - Terminals with factory fitted jumper links are tightened during production. Take care during installation to ensure factory fitted links are not lost by undoing both sides of linked terminals. After wiring, all terminal screws must be tightened to recommended torque specifications.
  - After installation of the switches the spacings between the terminals must be sufficient to fulfill the requirement of the applicable standards.

Operating temperature		
Min. Temperature [°C]		Max. Temperature [°C]
-25		60